

**CITY AND INDUSTRIAL DEVELOPMENT CORPORATION OF MAHARASHTRA LIMITED**

(CIN - U99999 MH 1970 SGC - 014574)

**REGD. OFFICE:**

"NIRMAL", 2nd Floor, Nariman Point,  
Mumbai - 400 021,  
PHONE : 00-91-22-6650 0900  
FAX : 00-91-22-2202 2509

**HEAD OFFICE:**

CIDCO Bhavan, CBD Belapur,  
Navi Mumbai - 400 614,  
PHONE: 00-91-22-6791 8100  
FAX : 00-91-22-6791 8166

Ref. No. CIDCO/Sr. Arch (Hsg/BP-IHP)/BP-IHP-31/2019/ **000105**

Date: **17 MAY 2019**

To,  
Superintending Engineer (Hsg-I),  
CIDCO, Maharashtra Ltd.,  
8<sup>th</sup> Floor, Raigad Bhavan,  
CBD, Belapur, Navi Mumbai-400614

Sub:- Amended Development Permission (Commencement Certificate adhering to Environmental Clearance) for proposed Mass Housing Scheme of EWS & LIG Residential Cum Commercial Buildings on Plot No.01, Sector- 37, Talaja Node, Navi Mumbai.

Ref :-

1. Commencement Certificate issued vide letter No.CIDCO/Sr.Arch(Hsg/BP-IHP)/ 2017/47, dtd. 28.09.2017
2. 1<sup>st</sup> Amended Fire NOC issued by Chief Fire Officer CIDCO vide letter No.CIDCO/FIRE/HQ/245/2018, dtd.03.07.2018
3. BGCTPL/SR.ARCH/CIDCO/1A&1B/2019/1605 dtd. 16/05/2019
4. CIDCO/SE(Hsg-I)/ACE(I&Metro)/2019/E-372 dtd. 17/05/2019

Dear Sir/Madam,

Please refer to your application for Amended Development Permission for Proposed Mass Housing Scheme of EWS & LIG Tenements with commercial building on Plot No.01, Sector- 37, Talaja Node, Navi Mumbai.

The Amended Development Permission is hereby granted to construct proposed Residential Cum Commercial Buildings on the plot mentioned above.

The Amended Commencement Certificate as required under section 45 to be read in conjunction with section 58 of the Maharashtra Regional and Town Planning Act, 1966, is enclosed herewith for the structures referred above.

Executive Engineer in-charge/Architect of the project shall adhere to and comply with the conditions of Commencement Certificate dated 18.09.2017

Executive Engineer in-charge/Architect of the project shall ensure the finished road edge level from Executive Engineer(PP-I),CIDCO and further to ensure that the finished plinth level of the proposed buildings to be minimum 750 mm above the proposed finished road edge level. In case, the building is having stilt, the finished stilt level to be minimum 300 mm. above the road edge level.

Executive Engineer in-charge of the project shall ensure that the recovery towards Construction & Other Workers Welfare Cess charges shall be made from Running Account Bills of the agency executing the subject work and same shall be deposited in the account of Government of Maharashtra directly with a copy of same to this office for record purpose.

The approval for plumbing services i.e. drainage and water supply shall be separately obtained by the applicant from the concerned Executive Engineer, CIDCO prior to the commencement of the construction Work.

You will ensure that the building materials will not be stacked on the road during the construction period.

The project contractor shall take all precautionary measures for prevention of Malaria breeding during the construction period of the project. If required, you can approach Health Department CIDCO, for orientation program and pest control at project site to avoid epidemic.

Thanking you,

Yours faithfully,



(T J Valdyia)

Sr. Arch.(Hsg./BP-IHP)/c

C.C. to: Architect, M/s B G Shirke Constn Tech. Pvt. Ltd,  
72-76, Mundhwa, Pune-411036.

**CITY & INDUSTRIAL DEVELOPMENT CORPORATION OF MAHARASHTRA LTD**  
**AMENDED COMMENCEMENT CERTIFICATE**

Permission is hereby granted under section – 45 to be read in conjunction with section 58 of the Maharashtra Regional and Town Planning Act, 1966 (Maharashtra XXXVII) of 1966 to **Superintending Engineer (Hsg-I), CIDCO Ltd., 8<sup>th</sup> Floor, Raigad Bhavan, CBD, Belapur, Navi Mumbai-400614**, as per the approved plans and subject to the following conditions for the development work of the **Proposed Mass Housing Scheme of EWS & LIG Tenements with commercial buildings on Plot No.-01, Sector- 37, Taloja Node, Navi Mumbai.**

**Total Proposed Built Up Area of 43172.73 Sq M. (Resi. BUA of 42242.81 SqM. + Comm. BUA of 929.92 SqM.).**

**LIG tenements = 810 Nos., EWS Tenements =438 Nos. Total Resi. tenements = 1248 Nos & Shop = 24 Nos.**

LIG type buildings: Total 10 Nos

**{ ( 4 Nos. C+R (G+14) : L-3 to L-6 ) + ( 4 Nos Resi ( G+13): L-2, L-8 to L-10 ) + ( 1 Nos Resi ( G+14): L-7 ) + ( 1 Nos Resi ( G+07): L-1 ) }**

EWS type buildings: Total 05 Nos

**{ ( 2 Nos. Resi.(G+ 13), E-1 to E-2) + ( 3 Nos. Resi.(G+ 14), E-3 to E-5) }**

- i. Applicant should construct Hutments for labors at site.
- ii. Applicant should provide drinking water and toilet facility for labors at site.

1. This Certificate is liable to be revoked by the Corporation if:-

- 1(a) The development work in respect of which permission is granted under this certificate is not carried out or the use thereof is not in accordance with the Sanctioned plans.
- 1(b) Any of the conditions subject to which the same is granted or any of the restrictions imposed upon by the corporation is contravened.
- 1(c) The Managing Director is satisfied that the same is obtained by the applicant through fraud or Misrepresentation and the applicant and/or any person deriving title under him, in such an event shall be deemed to have carried out the development work in contravention of section – 43 or 45 of the Maharashtra Regional and Town Planning Act- 1966.

2. The applicant shall-
  - 2(a) Give a notice to the Corporation for completion of development work up to plinth level, at least 7 days before the commencement of the further work.
  - 2(b) Give written notice to the Corporation regarding completion of the work.
  - 2(c) Obtain Occupancy Certificate from the Corporation.
  - 2(d) Permit authorized officers of the Corporation to enter the building or premises for which the permission has been granted, at any time for the purpose of ensuring the building control Regulations and conditions of this certificate.
3. The structural design, building materials, installations, electrical installations etc. shall be in accordance with the provision (except for provision in respect of floor area ratio) as prescribed in the National Building Code or and/or GDCRs- 1975 in force
4. The Certificate shall remain valid for period of 1 year from the date of its issue; thereafter revalidation of the same shall be done in accordance with provision of Section – 48 of MRTP Act- 1966 and as per regulations no. 16.1(2) of the GDCRs – 1975.
5. The conditions of this certificate shall be binding not only on the applicant but also on its successors and/or every person deriving title through or under him.
6. A certified copy of the approved plan shall be exhibited on site.
7. The amount of Rs. Nil /- deposited with CIDCO as security deposit shall be forfeited either in whole or in part at the absolute discretion of the Corporation for breach of any of the conditions attached to the permission covered by the Commencement Certificate. Such forfeiture shall be without prejudice to any other remedy or right of Corporation.
8. "Every Building shall be provided with underground and over head water tank. The capacity of the tanks shall be as per norms fixed by CIDCO. In case of high rise buildings underground and over head water tank shall be provided as per the fire fighting requirements of CIDCO. The applicant shall seek approval of the EE (Water Supply) of CIDCO in respect of capacity of domestic water tanks. The applicant shall seek approval of the Fire Officer of CIDCO in respect of capacity of water tanks for the fire fighting purpose".
9. You shall approach Executive Engineer, M.S.E.B. for the power requirements, location of transformer, if any, etc.
10. As per Govt. of Maharashtra memorandum vide No. TBP/4393/1504/C4-287/94, UD-11/RDP, Dated 19<sup>th</sup> July, 1994 for all buildings following additional conditions shall apply
  - i) As soon as the development permission for new construction or re-development is obtained by the Owners/Developer, he shall install a 'Display Board' on the conspicuous place on site indicating following details:
    - a) Name and address of the owner/developer, Architect and Contractor,
    - b) Survey Number/City survey Number, Plot Number/Sector & Node of Land under reference along with description of its boundaries.
    - c) Order Number and date of grant of development permission or re-development permission issued by the Planning Authority or any other authority.
    - d) Number of Residential flats/Commercial Units with areas.

- e) Address where copies of detailed approved plans shall be available for inspection.
- ii) A notice in the form of an advertisement, giving all the detailed mentioned in (i) above, shall be published in two widely circulated newspapers one of which should be in regional language.
11. As per the notification dtd. 14<sup>th</sup> September 1999 and amendment on 27<sup>th</sup> August 2003, issued by Ministry of Environment & Forest (MOEF), Govt. of India and as per Circular issued by Urban Development Deptt., Govt. of Maharashtra, vide No. FAR/102004/160/P. No. 27/UD-20, dtd. 27/02/2004, for all Buildings following additional condition shall apply. The Owners/Developer shall use Fly Ash bricks or blocks or tiles or clay fly ash bricks or cement fly ash bricks or blocks or similar products or a combination of aggregate of them to the extent of 100 % (by volume) of the total bricks, blocks & tiles as the case may be in their construction activity.
12. As directed by the Urban Development Deptt. Government of Maharashtra, under Section - 154 of MR & TP Act- 1966 and vide Provision No. TPB 432001/2133/CR-230/01/UD-11, dated 10/03/2005, for all buildings, greater than 300.00 Sq. m. following additional condition of Rain Water Harvesting shall apply.
- a) All the layout open spaces/amenities spaces of Housing Society and new construction /reconstruction / additions on plots having area not less than 300.00 Sq. m. shall have one or more Rain Water Harvesting structures having minimum total capacity as detailed in schedule (enclosed).  
Provided that the authority may approve the Rain water Harvesting Structures of specifications different from those in Schedule, subject to the minimum capacity of Rain Water Harvesting being ensured in each case.
- b) The owner/society of every building mentioned in the (a) above shall ensure that the Rain Water Harvesting structure is maintained in good repair for storage of water for non potable purposes or recharge of groundwater at all times.
- c) The Authority may impose a levy of not exceeding Rs. 100/- per annum for every 100 Sq. m. of built up area for the failure of the owner of any building mentioned in the (a) above to provide or to maintain Rain Water Harvesting structures as required under these byelaws.
13. Approval/NOC from MSEDCL for size and location of Electric Sub-station shall be submitted while applying for Occupancy Certificate.
14. You shall submit opinion of SP(S) regarding access points while applying for Occupancy Certificate.

15. You shall comply with the terms & conditions of 1<sup>st</sup> Amended provisional Fire NOC issued by Chief Fire Officer vide letter No.CIDCO/FIRE/HQ/245/2018, dtd.03/07/2018.
16. You shall comply with the guidelines/directives imposed by MOEF time to time and submit requisite before next stage of development, if any.



(T J Vaidya)  
Sr. Arch. (Hsg./BP-IHP)/I/c

C.C. TO: : Architect, M/s B G Shirke Constn Tech. Pvt. Ltd,  
72-76, Mundhwa, Pune-411036.

C.C. TO: Separately to: CUC /CSSO/EE (WS)/

SCHEDULE  
RAIN WATER HARVESTING

Rain Water Harvesting in a building site includes storage or recharging into ground of rain water falling on the terrace or on any paved or unpaved surface within the building site.

1. The following systems may be adopted for harvesting the rain water down from terrace and the paved surface.
  - (i) Open well of a minimum of 1.00 mt. dia and 6 mt. in depth into which rain water may be channeled and allowed after filtration for removing silt and floating material. The well shall be provided with ventilating covers. The water from the open well may be used for non potable domestic purposes such as washing, flushing and for watering the garden etc.
  - (ii) Rain water harvesting for recharge of ground water may be done through a bore well around which a pit of one meter width may be excavated up to a depth of at least 3.00 mt. and refilled with stone aggregate and sand. The filtered rain water may be channeled to the refilled pit for recharging the bore well.
  - (iii) An impervious surface/ underground storage tank of required capacity may be constructed in the setback or other open space and the rain water may be channeled to the storage tank. The storage tank shall always be provided with ventilating covers and shall have draw-off taps suitably placed so that the rain water may be drawn off for domestic, washing, gardening and such other purposes. The storage tanks shall be provided with an overflow.
  - (iv) The surplus rain water after storage may be recharged into ground through percolation pits or trenches or combination of pits and trenches. Depending on the geomorphological and topographical condition, the pits may be of the size of 1.20 mt. width X 1.20 mt. length X 2.00 mt. to 2.50 mt. depth. The trenches can be of 0.60 mt. width X 2.00 to 6.00 mt. length X 1.50 to 2.00 mt. depth. Terrace water shall be channeled to pits or trenches. Such pits or trenches shall be back filled with filter media comprising the following materials.
    - a) 40 mm stone aggregate as bottom layer upto 50% of the depth;
    - b) 20 mm stone aggregate as lower middle layer up to 20% of the depth;
    - c) Coarse sand as upper middle payer up to 20% of the depth;
    - d) A thin layer of fine sand as top layer;
    - e) Top 10% of the pits/ trenches will be empty and a splash is to be provided in this portion in such a way that roof top water falls on the splash pad.
    - f) Brick masonry wall is to be constructed on the exposed surface of pits/ trenches and the cement mortar plastered. The depth of wall below ground shall be such that the

wall prevents loose soil entering into pits/ trenches. The projection of the wall above ground shall at least be 15 cms.

g) Perforated concrete slabs shall be provided on the pits/trenches.

- (v) If the open space surrounding the building is not paved, the top layer up to a sufficient depth shall be removed and refilled with coarse sand to allow percolation of rain water into ground.
2. The terrace shall be connected to the open well/bore well/storage tank/recharge pit/trench by means of HDPE/PVC pipes through filter media. A valve system shall be provided to enable the first washings from roof or terrace catchment, as they would contain undesirable dirt. The mouths of all pipes and opening shall be covered with mosquito (insect) proof wire net. For the efficient discharge of rain water, there shall be at least two rain water pipes of 100 mm dia mtr. for a roof area of 100 Sq. mt.
  3. Rain water harvesting structures shall be sited as not to endanger the stability of building or earthwork. The structures shall be designed such that no dampness is caused in any part of the walls or foundation of the building or those of an adjacent building
  4. The water so collected/recharged shall as far as possible be used for non-drinking and non-cooking purpose.

Provided that when the rain water in exceptional circumstances will be utilized for drinking and/or cooking purpose, it shall be ensured that proper filter arrangement and the separate outlet for by passing the first rain-water has been provided.

Provided further that it will be ensured that for such use, proper disinfectants and the water purification arrangements have been made.